

Technical Data Sheet:

Engol 131 Degreaser

Application:

Engol 131 Degreaser is an effective and economical degreasing agent designed to remove oil, grease and grime on industrial machinery, It is suitable for the cleaning new components after storage, automotive engine cleaning and many other industrial and fleet applications.

Description:

A controlled drying, solvent based, water-washable degreasing fluid designed for most industrial and automotive applications. Blended with high-powered solvents and emulsifiers and mixable with water.

Key Advantages:

- Safety due to its high flash point.
- Powerful solvent action - readily dissolves or loosens oil and grease deposits.
- Minimum evaporation loss.
- Maximum efficiency due to controlled drying.
- Simple spray or brush application.
- Easily removed by water wash.
- Demulsibility aids operation or oils traps.

Caution:

- Not to be used on paintwork and rubber.
- Do not spray onto hot engine.
- Flammable, keep away from source of ignition.
- Store away from sunlight and heat.
- Avoid eye contact and skin contact.
- Wash hands thoroughly after use.

Typical Physical Characteristics:

Engol 131 Degreaser	
Flash Point, °C, Closed Cup	38
Specific Gravity	0.830
Appearance	Clear Green Liquid
Emulsification (10% in water)	Pass

*The values of the specifications shown in this table are typical values given as an indicator only.

Pack Sizes:

- 500 ml ,1 Litre, 5 Litre and 20 Litre Plastic Bottles
- 208 Litre Steel Drums
- 1000 Litre IBC

Health and Safety Information:

For recommendations on safe handling and use of this product, please refer to the Material Safety Data sheet available on www.engolgroup.com